

# Chain link fences – IDEAL®

- high quality fences made of steel wires with galvanized or galvanized + PVC finish
- round galvanized or galvanized + PVC posts with cap and tension wire clamp are recommended to be used for the assembly
- it is also recommended to use tension wires, binding wires, stretchers and posts with the same galvanized or galvanized + PVC finish

## IDEAL® galvanized + PVC 50

description	color	height (mm)	roll length (m)
eyelets 55 × 55 mm wire diameter 2,50 mm 15, 25 m long <b>compact roll</b> RAL 6005 – green, RAL 8014 – brown RAL 7016 – anthracite	green	1000	15
	green	1000	25
	brown	1000	25
	anthracite	1000	25
	green	1250	15
	green	1250	25
	brown	1250	25
	anthracite	1250	25
	green	1500	15
	green	1500	25
	brown	1500	25
	anthracite	1500	25
	green	1600	15
	green	1600	25
	brown	1600	25
anthracite	1600	25	
green	1800	15	
green	1800	25	
brown	1800	25	
anthracite	1800	25	
green	2000	15	
green	2000	25	
brown	2000	25	
anthracite	2000	25	



(tension wire not included; must be ordered separately)

Note: colour white, blue, grey – price on request.



## IDEAL® galvanized + PVC – round non-interlaced roll

description	color	height (mm)	roll length (m)
eyelets 55 × 55 mm wire diameter 2,50 mm RAL 6005 – green 15, 25 m long RAL 7016 – anthracite 25 m long <b>(including tension wire)</b>	green	1000	15
	green	1000	25
	anthracite	1000	25
	green	1250	15
	green	1250	25
	anthracite	1250	25
	green	1500*	15
	green	1500*	25
	anthracite	1500*	25
	green	1600*	15
	green	1600*	25
	anthracite	1600*	25
	green	1800*	15
	green	1800*	25
	anthracite	1800*	25
green	2000*	15	
green	2000*	25	
anthracite	2000*	25	



\* from a height of 1500 mm, it is recommended to add a center tensioning wire (not included in the package)

## IDEAL® galvanized + PVC 50 – SUPER

description	height (mm)
eyelets 55 × 55 mm wire diameter 3,00 mm 25 m long <b>compact roll</b> RAL 6005 – green <b>(tension wire not included; must be ordered separately)</b>	1000
	1250
	1500
	1600
	1800
2000	



## IDEAL® galvanized

description	height (mm)
eyelets 55 × 55 mm wire diameter 2,00 mm 25 m long <b>compact roll</b> <b>(tension wire not included; must be ordered separately)</b>	1000
	1250
	1500
	1600
	1800
2000	



## IDEAL® galvanized – round interlaced roll

description	height (mm)	roll length (m)
eyelets 55 × 55 mm wire diameter 2,00 mm 15 and 25 m long roll <b>(including tension wire)</b>	1000	15
	1000	25
	1250	15
	1250	25
	1500*	15
	1500*	25
	1600*	15
	1600*	25
	1800*	15
	1800*	25
2000*	15	
2000*	25	




\* from a height of 1500 mm, it is recommended to add a center tensioning wire (not included in the package)



USE: gardens, factories and warehouses...

## IDEAL® galvanized + PVC 45 – TENNIS

- offer for fencing of court to height 3,0;3,5; 4,0m
- fencing mesh in rolls according to standard dimensions of court (18 × 36 m), i.e. roll at 18 meters


description	height (mm)	roll length (m)
 eyelets 45 × 45 mm wire diameter 1,80/2,70 mm RAL 6005 – green	3000	18
	3500	18
	4000	18

## Posts and post supports IDEAL® galvanized + PVC – TENNIS


description	height (mm)	diameter (mm)
 round posts IDEAL® RAL 6005 – green post includes the plastic cap (no clamp for tensioning wire)	3750	60
	4300	60
	4900	60
	5200	60
 post supports IDEAL® RAL 6005 – green including plastic cap and fasteners	3500	48
	4000	48
	4750	48

## Wicket IDEAL® galvanized + PVC – TENNIS

description	height (mm)	width (mm)
wicket IDEAL® TENNIS for tennis courts RAL 6005 – green frame made of round sections (closed) square mesh paneling eyelets 45 × 45 mm wire diameter 2,70 mm wicket consists of 2 posts, including pivot hinges included is the lock with FAB lock insert	2200	1250



## Tension wire IDEAL® galvanized + PVC

description	color	length (m)
roll 26, 52 and 78 m wire diameter 3,40 mm RAL 6005 – green RAL 8014 – brown RAL 7016 – anthracite 	green	26 (green label)
	green	52 (white label)
	green	78 (green label)
	brown	52 (white label)
	brown	78 (green label)
	anthracite	52 (white label)
	anthracite	78 (green label)



## Tension wire galvanized

description	length (m)
roll 52 and 78 m wire diameter 3,00 mm	52 (white label)
	78 (green label)



### RECOMMENDATION:

- no center tension wire technologically possible to interlock during production and must be stretched independently
- center tension wire is included with meshes with height beginning at 1,5 m



## Accessories for the installation of chain link fence

description	
 tensioner with galvanized finish	
 tensioner with galvanized + PVC finish RAL 6005 – green	green
 RAL 8014 – brown	brown
 RAL 9010 – white	white
 RAL 5010 – blue	blue
 RAL 7016 – anthracite	anthracite
 tensioner SUPER with galvanized + PVC finish – green	
 KOMBI galvanized tensioner	
 KOMBI galvanized + PVC tensioner	
 tension comb IDEAL® for stretching square meshes having heights up to 1500 mm (in primer coat)	
 tension comb IDEAL® for stretching square meshes having heights above 1500 mm (in primer coat)	
 pliers IDEAL® PROFI	
 brace IDEAL® galvanized	
 brace IDEAL® galvanized	
 brace IDEAL® galvanized + PVC RAL 6005 – green	
 brace IDEAL® galvanized + PVC RAL 6005 – green	
 brace IDEAL® galvanized + PVC RAL 7016 – anthracite	
 brace IDEAL® galvanized + PVC RAL 7016 – anthracite	

## Binding wires

description	wire thickness (mm)	length (m)
 galvanized binding wire in wired case	1,0	100
	1,2	100
 galvanized binding wire	1,0	24
	1,4	50
	1,8	50
 galvanized + PVC RAL 6005 binding wire in wired case – green	1,4	60
 binding wire galvanized + PVC RAL 6005 with cutoff, flat – green	–	100
 binding wire + PVC RAL 6005 – green	1,4	24
 binding wire galvanized + PVC RAL 6005 – green	1,4	50
 RAL 8014 – brown	1,4	50
 RAL 9010 – white	1,4	50
 RAL 7016 – anthracite	1,4	50
 binding wire galvanized + PVC – green	2,6	25
 binding wire galvanized (2 pcs in package)	0,65	–
 binding wire galvanized and varnished RAL 6005 – green (2 pcs in package)	0,65	–