


Posts and post supports




Round posts – IDEAL














- strongly galvanized
- the technologies we use ensure at least **double the corrosion resistance** on iron and galvanized materials (salt fog testing in a chamber)
- this is the **highest level of surface treatment** and painting in the Czech Republic

| description | height/diameter/wall thickness (mm) |
|--|-------------------------------------|
|  POST galvanized | 1750/38/1,25 |
|  black plastic cap | 2000/38/1,25 |
|  black tension wire clamp | 2300/38/1,25 |
|  clamp included with post | 2600/38/1,50 |
|  included with post | 1500*/48/1,50 |
|  * tension wire clamp is not included with post | 1750*/48/1,50 |
|  | 2000*/48/1,50 |
|  | 2100/48/1,50 |
|  | 2400/48/1,50 |
|  | 2600/48/1,50 |
|  | 3000/48/1,50 |
|  POST galvanized + PVC green plastic cap | 1750/38/1,25 |
|  green plastic cap | 2000/38/1,25 |
|  green tension wire clamp | 2300/38/1,25 |
|  clamp included with post | 2600/38/1,50 |
|  included with post | 1500*/48/1,50 |
|  RAL 6005 – green | 1 750*/48/1,50 |
|  | 2000*/48/1,50 |
|  * tension wire clamp is not included with post | 2100/48/1,50 |
|  | 2400/48/1,50 |
|  | 2600/48/1,50 |
|  | 3100/48/1,50 |
|  | 1 750*/48/1,50 |
|  POST galvanized + PVC black plastic cap | 2000*/48/1,50 |
|  black plastic cap | 2400*/48/1,50 |
|  RAL 7016 – anthracite | 2600*/48/1,50 |
|  * tension wire clamp is not included with post | |

Roundpostsupports – IDEAL®


- strongly galvanized
- post supports are cut on the top to be anchored to posts with plastic ends
- bonding material is included
- **IDEAL®** post supports are also used for **PILCLIP®** posts




| description | height/diameter/wall thickness (mm) |
|--|-------------------------------------|
|  POST SUPPORT galvanized | 1 750/38/1,25 |
|  | 2000/38/1,25 |
|  | 2500/38/1,25 |
|  POST SUPPORT galvanized + PVC RAL 6005 – green | 1 750/38/1,25 |
|  | 2000/38/1,25 |
|  | 2500/38/1,25 |
|  | 2700/38/1,50 |
|  | 3000/38/1,50 |
|  | 3000/48/1,50 |
|  POST SUPPORT galvanized + PVC RAL 7016 – anthracite | 2000/38/1,2 |
|  | 5 |
|  | 2500/38/1,2 |
|  | 5 |




Square posts for PILOFOR® panels



PILOFOR® posts 60 × 60 mm for PILOFOR® panels

| description | height of post (mm) | galvanized | galvanized + PVC RAL 6005 | galvanized + PVC RAL 7016 |
|--|---|------------|---------------------------|---------------------------|
|  <p>square section 60 × 60 mm wall thickness 1,50 mm posts are provided with pressed M6 nuts and black PVC cap RAL 6005 – green</p> <p>●</p> <p>□</p> | 1500 | □ | □ | – |
| | 1700 | □ | □ | □ |
| | 2000 | □ | □ | □ |
| | 2200 | □ | □ | – |
| | 2400 | □ | □ | □ |
| | 2600 | □ | □ | □ |
| | 2800 | □ | □ | – |
| | 3000 | □ | □ | – |
| | 3200 | □ | □ | – |
| | Other colors of posts can be ordered separately. | | | |


PILODEL® posts 60 × 40 mm for PILOFOR® panels


| description | height of post (mm) | galvanized | galvanized + PVC RAL 6005 | galvanized + PVC RAL 7016 | |
|---|---|------------|---------------------------|---------------------------|--|
|  <p>rectangular section 60 × 40 mm wall thickness 1,50 mm posts are provided with black PVC cap RAL 6005 – green, RAL 7016 – anthracite</p> <p>● ●</p> <p>□</p> | 1500 | □ | □ | – | |
| | 1700 | □ | □ | □ | |
| | 2000 | □ | □ | □ | |
| | 2200 | □ | □ | □ | |
| | 2400 | □ | □ | □ | |
| | 2600 | □ | □ | □ | |
| | 3000 | □ | □ | – | |
| | 3200 | □ | □ | – | |
| | Other colors of posts can be ordered separately. | | | | |

Posts with fixation strip PILCLIP®

- the technologies we use ensure at least **double the corrosion resistance** on iron and galvanized materials (salt fog testing in a chamber)
- this is the **highest level of surface treatment** and painting in the Czech Republic
- thanks to the pressed “V” shaped beam, the PILCLIP® post has much **greater rigidity and solidity** compared to common round posts (e.g. the PILCLIP® 48 mm in diameter is equivalent to a common round post with a diameter of 60 mm)
- installing fences** on PILCLIP® posts is **more sophisticated and convenient for the user** compared to round posts



| description | height/diameter/wall thickness (mm) |
|---|-------------------------------------|
|  <p>POST galvanized + PVC green PVC cap included with post RAL 6005 – green</p> <p>●</p> <p>○</p> | 1700/48/1,50 |
| | 2000/48/1,50 |
| | 2300/48/1,50 |
| | 2500/48/1,50 |
| | 2700/48/1,50 |
| | 3000/48/1,50 |

| description | height/diameter/wall thickness (mm) |
|--|-------------------------------------|
|  <p>POST galvanized + PVC black PVC cap included with post RAL 7016 – anthracite</p> <p>●</p> <p>○</p> | 1700/48/1,50 |
| | 2000/48/1,50 |
| | 2300/48/1,50 |
| | 2500/48/1,50 |